



## Lindy 39385 estensore KVM Trasmettitore e ricevitore

Marchio : Lindy

Codice prodotto: 39385

Nome del prodotto : 39385

Lindy 39385. Tipo: Trasmettitore e ricevitore, Tecnologia di connessione: Cablato, Distanza massima di trasferimento: 150 m. Tipo di porta video del trasmettitore: DisplayPort, Tipo di porta video locale del trasmettitore: DisplayPort, Tipo di porta per mouse/tastiera locale del trasmettitore: USB. Tipo di porta video locale del ricevitore: DisplayPort, Tastiera locale del ricevitore/tipo di porta per mouse: USB. Tipo di porta USB: USB Type-A/USB Type-B. Corrente d'ingresso: 1 A, Tensione CC: 24 V



Features		Power	
Type *	Transmitter & receiver	Input current	1 A
Connectivity technology *	Wired	DC-in jack	✓
Maximum transfer distance	150 m	DC voltage	24 V
Cable types supported	Cat6	<b>Weight &amp; dimensions</b>	
Maximum digital resolution	3840 x 2160 pixels	Transmitter width	14 cm
Maximum refresh rate	60 Hz	Transmitter depth	6.5 cm
Colour depth	8 bit	Transmitter height	1.8 cm
Product colour	Black	Transmitter weight	800 g
Material	Metal	Receiver width	14 cm
LED indicators	Power	Receiver depth	6.5 cm
<b>Transmitter</b>		Receiver height	1.8 cm
Transmitter video port type	DisplayPort	Receiver weight	800 g
Transmitter local video port	✓	<b>Packaging data</b>	
Transmitter local video port type	DisplayPort	Package width	245 mm
Transmitter local keyboard/mouse port type	USB	Package depth	75 mm
RJ-45 ports quantity (transmitter)	1	Package height	185 mm
<b>Receiver</b>		Package weight	1.02 kg
Receiver local video port type	DisplayPort	<b>Packaging content</b>	
Receiver local keyboard/mouse port type	USB	AC adapter included	✓
RJ-45 ports quantity (receiver)	1	Cables included	USB
Receiver local video ports quantity	1	Manual	✓
<b>Ports &amp; interfaces</b>		Mounting bracket(s) included	✓
USB port type	USB Type-A/USB Type-B	Included power plug types	AU, EU, UK, US
RS-232 ports	2	<b>Operational conditions</b>	
USB 1.1 ports quantity	5	Operating temperature (T-T)	0 - 40 °C
Remote (IR) input	2	Storage temperature (T-T)	-20 - 60 °C

Ports & interfaces		Operational conditions	
Remote (IR) output	2	Operating relative humidity (H-H)	20 - 90%
		Storage relative humidity (H-H)	20 - 90%
Sustainability			
Sustainability compliance		✓	
Other features			
Compliance certificates		Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS	



4002888393850

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-APR-2025. Prints or copies of Information are only valid on the printed Publication date