

Lindy 43319 replicatore di porte e docking station per laptop Cablato USB 3.2 Gen 1 (3.1 Gen 1) Type-C Nero

Marchio : Lindy

Codice prodotto: 43319

Nome del prodotto : 43319

- Si connette a un tablet, MS Surface* o Ultrabook tramite cavo USB tipo C
- Aggiunge 3 porte USB di tipo A (2x USB 3.2 Gen 2 10Gbps, 1x USB 2.0), una porta USB di tipo C per dati e alimentazione, una porta HDMI e una porta Gigabit Ethernet
- Si collega al tablet/ultrabook utilizzando il supporto estensibile
- Supporta risoluzioni fino a 4K Ultra HD 30Hz

Mini Docking Station USB 3.2 Gen 2 Tipo C - HDMI, PD 3.0 100W, USB 3.2 Gen 2, Gigabit

Lindy 43319. Tecnologia di connessione: Cablato, Interfaccia host: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Fornitura di alimentazione USB fino a: 100 W. Velocità trasferimento Ethernet LAN: 1000 Mbit/s. Colore del prodotto: Nero, Velocità di trasferimento dati: 0,48 Gbit/s, Risoluzione (digitale massima): 3840 x 2160 Pixel. Tipologia alimentazione: USB, Voltaggio di uscita: 20 V, Corrente d'uscita: 5 A. Larghezza: 223 mm, Profondità: 32 mm, Altezza: 33 mm



Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	3
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
USB Power Delivery (USB PD)	✓
USB Power Delivery up to	100 W
HDMI ports quantity *	1
HDCP	✓
HDCP version	1.4/2.2

Network

Ethernet LAN *	✓
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	1000 Mbit/s

Performance

Data transfer rate	0.48 Gbit/s
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	30 Hz
Product colour *	Black
Housing material	Plastic
Certification	CE, FCC, CP65

Power

Power source type	USB
Output voltage	20 V
Output current	5 A

Operational conditions

Operating temperature (T-T)	-20 - 70 °C
Storage temperature (T-T)	-20 - 85 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	223 mm
Depth	32 mm
Height	33 mm
Weight	160 g

Packaging data

Package width	280 mm
Package depth	110 mm
Package height	45 mm
Package weight	250 g

Packaging content

Manual	✓
--------	---

Technical details

Compliance certificates	REACH, RoHS
-------------------------	-------------

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------



4002888433198

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAR-2025. Prints or copies of Information are only valid on the printed Publication date