



Acer X138WH Projector met normale projectieafstand 3700 ANSI lumens DLP WXGA (1280x800) 3D Zwart

Merk : Acer

Artikelcode: MR.JQ911.001

Productnaam : X138WH

Acer X138WH. Projector helderheid: 3700 ANSI lumens, Projectietechnologie: DLP, Projector native resolution: WXGA (1280x800). Type lichtbron: Lamp, Levensduur van de lichtbron: 4000 uur, Levensduur van de lichtbron (besparingsmodus): 10000 uur. Focus: Handmatig, Brandpuntbereik: 21.85 - 24 mm, Diafragma (F-F): 2,41 - 2,53. Formaat analoog signaal: NTSC, NTSC 3.58, NTSC 4.43, PAL, PAL B, PAL D, PAL G, PAL H, PAL I, PAL M, PAL N, SECAM, SECAM B,..., Ondersteunde grafische resoluties: 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1152..., Ondersteunde video-modi: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. HDMI-connector type: Volledige grootte, HDMI versie: 1.4a

Projector		Opslagmedia	
Ondersteunde beeldverhoudingen	4:3, 16:10, 16:9	Geïntegreerde geheugenkaartlezer *	✗
Geschikt voor schermmaten *	736,6 - 7620 mm (29 - 300")	Kenmerken	
Projectie-afstand objectief	1,1 - 10 m	Geluidsniveau (spaarzame modus)	24 dB
Projector helderheid *	3700 ANSI lumens	HDCP	✓
Projectietechnologie *	DLP	Projectiemodi	Voorkant, Achter
Projector native resolution *	WXGA (1280x800)	Preset modes	3D, Helder, Bioscoop, Spel, Presentatie, Standaard, Vivid photo, sRGB
Typische contrastverhouding *	20000:1	On Screen Display (OSD)	✓
Oorspronkelijke beeldverhouding *	16:9	Geluidsniveau *	30 dB
Aantal kleuren	1.073 biljoen kleuren	Luchtfilter	✓
Projector helderheid (spaarzame modus)	2960 ANSI lumens	Wachtwoordbeveiliging	✓
Frequentiebereik horizontaal	15 - 100 kHz	Password bescherming	Supervisor, Gebruiker
Frequentiebereik verticaal	24 - 120 Hz	Ruisonderdrukking	✓
Digitale gamma correctie	✓	Bestandsdeling ondersteunt	✓
Keystone correctie, verticaal	-40 - 40°	Multimedia	
Matrix grootte	1,65 cm (0.65")	Ingebouwde luidsprekers *	✓
Matrix type	DMD	Gemiddeld vermogen	3 W
Horizontale synchronisatie (min)	15 kHz	Aantal ingebouwde luidsprekers	1
Horizontale synchronisatie (max)	100 kHz	Design	
Verticale synchronisatie (min)	0,024 kHz	Type product *	Projector met normale projectieafstand
Verticale synchronisatie (max)	0,12 kHz	Kleur van het product *	Zwart
Lichtbron		Materiaal behuizing	Kunststof
Type lichtbron *	Lamp	Plaatsing	Desktop, Plafond
Levensduur van de lichtbron *	4000 uur	LED-indicatoren	✓
Levensduur van de lichtbron (besparingsmodus)	10000 uur	Bevestigingsmogelijkheid voor kabelslot	✓
Soort lamp	OSRAM	Kabelslot sleuf type	Kensington
Lampvermogen	203 W	Beeldscherm	
Aantal lampen	1 lampen	Ingebouwd display *	✗
Lensysteem		Energie	
Focus *	Handmatig	Stroombron *	AC
Brandpuntbereik	21.85 - 24 mm	Stroomverbruik (typisch) *	240 W
Diafragma (F-F)	2,41 - 2,53	Stroomverbruik (in standby) *	0,5 W
Zoomcapaciteit	✓	Verbruik (modus Economisch)	195 W
Zoom type	Handmatig	AC-ingangsspanning	100 - 240 V
Zoomverhouding	1.1:1	AC-ingangsfrequentie	50 - 60 Hz
Digitale zoom	2x		
Optische zoom	1,1x		
Throw ratio	1.54 - 1.72:1		

Video		Energie	
Formaat analogo signaal *	NTSC, NTSC 3.58, NTSC 4.43, PAL, PAL B, PAL D, PAL G, PAL H, PAL I, PAL M, PAL N, SECAM, SECAM B, SECAM D, SECAM G, SECAM H, SECAM K, SECAM K1, SECAM L	Voltage tolerantie	10 procent
Volledige HD *	✓	Stroomvoorziening via USB	✓
3D *	✓	Software	
3D Ready	✓	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
Ondersteunde grafische resoluties	640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1152 x 870, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Ondersteunt Windows	
Ondersteunde video-modi	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video kleurenmodi	Auto, Bright Cinema, Bioscoop, Spel, Presentatie, sRGB		
Poorten & interfaces			
HDMI-connector type	Volledige grootte		
HDMI versie	1.4a		
Aantal USB 2.0-poorten	1		
Audio-ingang (L, R) *	1		
PC-ingang (D-Sub)	✓		
VGA (D-Sub)poort(en) *	1		
Aantal HDMI-poorten *	1		
Composiet video-ingang *	1		
DVI-poort *	✗		
Mobile High-Definition Link (MHL)	✓		
Ingang stroom	✓		
Netwerk			
Ethernet LAN *	✗	Mac-compatibiliteit	✓
Wifi *	✗	Ondersteunt Mac-besturingssysteem	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Eisen aan de omgeving			
Bedrijfstemperatuur (T-T)			0 - 40 °C
Relatieve vochtigheid in bedrijf (V-V)			0 - 80 procent
Gewicht en omvang			
Breedte			313 mm
Diepte			240 mm
Hoogte			113,7 mm
Gewicht *			2,7 kg
Breedte verpakking			400 mm
Diepte verpakking			340 mm
Hoogte verpakking			168 mm
Gewicht verpakking			3,81 kg
Inhoud van de verpakking			
Afstandsbediening inbegrepen *			✓
Afstandsbediening			IR
3D brillen meegeleverd			✗
Meegeleverde kabels			AC
Snelstartgids			✓

Technische details

Kleur ✓

Logistieke gegevens

Code geharmoniseerd systeem (HS) 85286200

Overige specificaties

Kleurtemperatuur 4000 K
Aantal lampen 1 gloeilamp(en)



4713883467360

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.